SAUNAHEATER TYPE 44 AND TYPE GSK 44





Saunaheater - Standing model for private and commercial use in home and business saunas.

Saunaheater in clear classic design. The proven construction for decades in a double-casing execution with large ventilation cross-section offers best sauna thermic for every requirement.

The large air flow ensures a dry and optimal sauna climate.

It results in an extremely short warm-up time of the sauna room, and it also convinces by low-noise operation.

This means an environmentally friendly and economical operation of your sauna.

Optional equipment:

- ◆ "GSK" Version = Greater Stone Kontainer for more effective infusions
- Heater railing made of wood (all 4 sides possible)

Technical Datas:

Outer casing: optionally "real Enamel" – anthracite-colored

(scratch-resistant, temperature-resistant, odorless)

or in Chromium-steel (shiny – covered with a protection-foil).

Top-frame: Stainless steel, brushed

Stone-basket: Stainless steel, reinforced with "V-angle-struts", without contact to the heating-elements

galvanized-steel – optional in outer casing version

Rear/Backside: galvanized-ste Radiator carrier sheet: Chrome-steel Inner casing: Chrome-steel

Foot-frame: Chrome-steel, with drip protection Electric connection: integrated, by 2 screws fixed rear panel

Heating elements: á 1000 watts, very low heating rod load (3,2 watts/cm²) and long life term

Heating capacities: 10 | 12 and 15 kW - 2 Power circuit

Power connection: 400V 3N AC

Dimensions (WxDxH): $44 \times 44 \times 75 / GSK$: H = 82 cm

Safety distance: minimum 10 cm on all sides to flammable parts

Stone filling: approx. 20 kg / GSK: ca. 35 kg

Heater weight net: approx. 30 kg

Recommended room size of the sauna cabin according to the table. (Basic = RAL-Guideline for sauna cabins in buildings)

9-7			
Heating-power kW	10	12	15
Suitable for Sauna cabins m ³	10 – 15	14 – 18	17 – 24

Technical alterations reserved.