



A varied Combined – Wall-Saunaheater for the private and moderate commercial use in home and business saunas.

Wall-Saunaheater made entirely of stainless steel in a classic and noble design. Double-casing construction. Outer-casing in Chromium-steel, shiny.

Junction-box on the backside, Base as a drip tray. The vaporizer, open, next to the sauna stones, provides a strong and concentrated steam discharge.

Separate vaporizer (W10) with integrated steam deflector in the wall mounted bracket.

Vaporizer (W10) fully assembled via connection terminal in the oven and drain device with drain valve.

Technical Datas:

Outer casing:	Chromium-steel (shiny – covered with a protection-foil).
Stone-basket frame:	Stainless steel, brushed; Steam-box in stainless steel;
Stone-support grid:	Chrome-steel
Inner casing:	Chrome-steel
Electric connection:	Junction-box on the backside
Heating elements:	only á 1500 watts
Heating capacities:	4,5 6,0 7,5 and 9,0 kW
Power connection:	400V 3N AC
Vaporizer (W10):	Casing in Chromium-steel (shiny); Head plate in stainless steel, brushed; Steam-box in stainless steel; with a drain-valve 3/8" and a dry-run-protection-sensor with acoustic warner. Inclusive a Aroma-tray + Aroma-mug in stainless steel.
Vaporizer power:	1500 W – 230V 1N AC
Steam-box filling:	ca. 5 Litre
Steam output:	ca. 2,4 kg/h
Dimensions (WxDxH):	42 x 39 x 60 cm
Safety distance:	minimum 7 cm to flammable parts – Heater sides and front
Stone filling:	ca. 18 kg
Heater weight net:	ca. 20 kg

Recommended room size of the sauna cabin according to the table. (Basic = RAL-Guideline for sauna cabins in buildings)

Heating-power kW	4,5	6,0	7,5	9,0
Suitable for Sauna cabins m ³	4 – 6	6 – 8	7 – 10	9 – 12